



Interior dimensions:

47.1 x 25.2 x 27.7 cm
(18.54" x 9.92" x 10.92")

- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalisation Valve
- Comfortable rubber over-moulded handles
- Stainless steel hardware and padlock protectors
- Pick N Pluck™ foam
- Personalised nameplate service available
- Unconditional Guarantee of Excellence

Black OD Green Desert Tan
Black OD Green* Desert Tan

1460 Case SPECIFICATIONS

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)
52.9 x 32.3 x 32.4 cm (20.85" x 12.73" x 12.75")	47.1 x 25.2 x 27.7 cm (18.54" x 9.92" x 10.92")

Lid Depth	Bottom Depth	Total Depth
12.5 cm (4.91")	15.3 cm (6.01")	27.7 cm (10.92")

Weight w/Foam	Weight w/o Foam	Buoyancy Max.
5.66 kg. (12.48 lbs)	3.97kg (8.75 lbs.)	37.19 kg (82 lbs.)

Range Temperature
-40 / 99° C (-40 / 210° F)

1460 Case Certificates

- IP67(1 meter submersion for 30 minutes)

Configurations

Cat. #	Description
1460	
1460NF	1460 Case (No foam)
1460AALG	1460 Case (with custom foam for 9430/9435)

Materials

Body	Latch	Lid O-Ring	Pins
Polypropylene	EXL	Polymer	Stainless steel

Foam	Purge Body	Purge Vent	Purge O-Ring
Polyurethane 6 pieces	ABS	3 M Hydrophobic Nonwoven PET	70 s Nitrile

1460 Case Accessories

Cat. #	Description
1461	Replacement Foam Set
1463	Replacement O-ring